



Basic Fit

Basic Fit is the “original” recycled rubber fitness floor. Available in rolls and tiles, this durable surface sets the standard for performance, quality, and affordability.



MARKETS

- Fitness
- Student Rec

BENEFITS

- Durable
- Sustainable
- Slip-resistant
- Ease of maintenance

APPLICATIONS

- Free Weights
- Therapy / Rehab
- Retail
- Public Spaces
- Strength Equipment
- Selectorized Strength
- Childcare / Playzones
- K-12 / Higher Education
- Cardio
- Ice

PRODUCT INFORMATION

Nominal Dimensions:

Available as a standard in rolls and interlocking tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.



8mm x 48" (1.2m)
6mm x 48" (1.2m)
9mm x 48" (1.2m)



8mm x 23" (58cm) x 23" (58cm)

Color Options:

[Click here to view colors](#)

THE NRG FACTOR

NRG =



9.98%

Force Reduction
Absorption of impact energy



71.9%

Energy Restitution
Useful return of impact energy



Safety



Ergonomics



Acoustics

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Static Load Limit	ASTM F970	0.020" (@1000psi)
Coefficient of Friction	ASTM D2047	> 0.9
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	<1g, 1,000 cycles
Pill Test	ASTM D2859	Pass
Impact Insulation Class*	ASTM E492	51
Delta IIC*	ASTM E2179	22

*Tested on a 6" concrete slab with no ceiling.