



# Performance Rally

Performance Rally is a 14.5mm surface tailored for heavy conditioning and is available in both rolls and interlocking tiles.



## MARKETS

- Fitness
- Sports
- Student Rec

## BENEFITS

- Durable
- Sustainable
- Ease of maintenance
- Slip-resistant

## APPLICATIONS

- Selectorized Strength
- Free Weights
- Cardio
- Therapy / Rehab
- Retail
- Public Spaces
- Childcare / Playzones
- K-12 / Higher Education
- Corporate / Offices

## PRODUCT INFORMATION

### Nominal Dimensions:

Available as a standard in rolls and interlocking tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.



14.5mm (2.5mm+12mm) x 48" (1.2m)



14.5mm (2.5mm+12mm) x 23" (58cm) x 23" (58cm)

### Color Options:

[Click here to view colors](#)

## TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Static Load Limit	ASTM F970	0.009" (@ 250psi)
Coefficient of Friction	ASTM D2047	> 0.9
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	< 1g, 1,000 cycles
Pill Test	ASTM D2859	Pass
Standard Vertical Deformation	ASTM F2772	2.66mm
Surface Effect Slip Resistance	ASTM F2772	Pass
Ball Rebound	ASTM F2772	98.8%
Force Reduction	ASTM F2772	35.7%
Impact Insulation Class*	ASTM E492	58
Delta IIC*	ASTM E2179	27

\*Tested on a 6" concrete slab with no ceiling.

## THE NRG FACTOR

NRG =



**35.4%**

**Force Reduction**  
Absorption of impact energy



**53.7%**

**Energy Restitution**  
Useful return of impact energy



Safety



Ergonomics



Acoustics

